



**TURNSTILES.us™**

**SECURING THE U.S. and the GLOBE**

**AG-36-ADA**

**FULL HEIGHT ADA GATE**

**INSTALLATION INFORMATION**



## **INSTALLATION PROCEDURE**

- 1. THE ADA GATE ARRIVES PRE-ASSEMBLED AND READY TO INSTALL ON A LEVEL SURFACE**
- 2. IF USING AN ELECTRIC STRIKE LOCATE THE PASSAGES USED FOR ELECTRICAL WIRING TWO HOLES AT THE TOP OF THE ADA GATE INSIDE THE MOUNTING BRACKETS ON THE FRAME, AND THROUGH THE FEET THAT STICK OUT PASSED THE THRESHOLD. DETERMINE ELECTRICAL WIRING METHOD. (STRIKE DIAGRAM FOUND LATER IN THIS MANUAL)**
- 3. CORE DRILLING AND FILLING WITH CONCRETE IS REQUIRED FOR THE FEET. IF YOU DO NOT WISH TO CORE DRILL YOU MAY CUT OFF THE FEET BUT THIS IS NOT RECOMMENDED UNLESS THE FRAME IS MOUNTED SOLID ON BOTH SIDES WITH THE MOUNTING BRACKETS. USE THE 1/2" ANCHORS PROVIDED IN THE 4 CORNERS OF THE THRESHOLD AND THE COUNTERSINK TAPCONS IN THE LIPS OF THE THRESHOLD.**
- 4. ONCE THE GATE IS STANDING ADJUST HYDRAULIC SELF CLOSING HINGE (ADJUSTMENT INFORMATION FOUND LATER IN THIS MANUAL)**

## HARDWARE SPECIFICATIONS

### ● HINGE SPECS

- SELF-CLOSING HINGE WITH PATENTED HYDRAULIC DAMPING
- ADJUSTABLE CLOSING SPEED & CLOSING PRESSURE
- EASY MOUNTING WITH QUICK-FIX
- ADJUSTABLE FREE RUN FOR PERFECT CLOSING (FINAL SNAP)
- FOR LEFT AND RIGHT OPENING GATES
- OPENING ANGLE: 180°
- POWDER COATED ALUMINUM CASING
- DOUBLE STAINLESS-STEEL BEARING
- 2-DIMENSIONALLY ADJUSTABLE (2 X 20 MM)
- EASY TO OPEN: MAX. 15 NM OF FORCE
- CONFORMS TO ALL REGULATIONS REGARDING MAX ALLOWED FORCES TO OPEN GATES
- IDEAL IN COMBINATION WITH MAGNETIC AND MECHANICAL LOCKS
- BOTTOM DINO HINGE INCLUDED (DOUBLE STAINLESS BEARING)
- ESPECIALLY DESIGNED FOR EXTERIOR USE: RAIN & FROST-PROOF
- AESTHETIC DESIGN
- BURGLAR PROOF AND ANTI-THEFT
- CLOSING FORCE OVER THE FULL 180° OPENING ANGLE
- CLOSING SPEED UNAFFECTED BY TEMPERATURE CHANGES
- FOR GATES UP TO 150 KG (MAX 1,5 M WIDE)
- TESTED AT 500.000 MOVEMENTS
- TESTED FROM -30 °C UP TO +7

### ● STRIKE SPECS

- TYPE SE.EH: - FAIL SECURE
- TYPE SE.RH: - FAIL OPEN (FAIL SAFE)
- EXTREMELY STRONG AND USER-FRIENDLY DESIGN
- EASY LEFT OR RIGHT HAND CHANGING
- FOR PROFILES 2" AND LARGER
- VOLTAGE: 12 V AC/DC
- CURRENT : 1 A
- CURRENT: 1.5 A
- WATER RESISTANT, WEATHERPROOF
- PRESSURE RESISTANCE ON SELF-LATCHING BOLT: 1000 LBS

## LOCK AND LATCH ASSEMBLY SPECS

- ISO 9227 KTL / E-COATED LOCKBOX WITHSTANDS 1000 HOURS OF SALT SPRAY TEST
- EASY LEFT OR RIGHT CHANGING OF THE SELF-LATCHING DEAD BOLT
- THROW OF THE DEADBOLT, 7/8" IN 1 TURN OF THE KEY
- KEY-OPERATED SELF-LATCHING BOLT, ALLOWS FREE EXIT APPLICATION
- 4-HOLE MOUNTING WITH TWO HEX HEAD SOCKET SCREWS
- CENTER DISTANCE BOLTS: 2 - 3/8"
- ADJUSTMENT OF THE BOLTS UP TO 3/4" CONTINUOUS WITHOUT REMOVING THE LOCKBOX
- STAINLESS STEEL MECHANISM

## PUSH BAR ASSEMBLY

- ANODIZED BLACK, ALUMINUM PUSH BAR WITH STAINLESS STEEL MECHANISM
- COMPATIBLE WITH LOCINOX LA AND LF CHASSIS
- PRESSING THE PUSH BAR OPERATES THE DEAD BOLT
- IDEAL IN COMBINATION WITH FREE VINCI LOCK
- FOR LEFT AND RIGHT TURNING GATES
- EASY TO INSTALL ON THE GATE WITH QUICK-FIX
- DELIVERED WITH BLINDED 5/16" FOLLOWER
- POSSIBLE TO COMBINE WITH HALF HANDLE SETS WITH 5/16" FOLLOWER
- MAXIMUM WIDTH: 4-1/2 FT.
- PUSH BAR LENGTH - STANDARD 45-1/4" (CAN BE SHORTENED)
- DUMMY CYLINDER RECOMMENDED

## **WARRANTY AND DISCLAIMER**

### **WARRANTY**

THIS LIMITED WARRANTY APPLIES TO PHYSICAL GOODS, AND ONLY FOR PHYSICAL GOODS, PURCHASED FROM WE.

### **WHAT DOES THIS LIMITED WARRANTY COVER?**

THIS LIMITED WARRANTY COVERS ANY DEFECTS IN MATERIAL OR WORKMANSHIP UNDER NORMAL USE DURING THE WARRANTY PERIOD.

DURING THE WARRANTY PERIOD, WE WILL REPAIR OR REPLACE, AT NO CHARGE, PRODUCTS OR PARTS OF A PRODUCT THAT PROVES DEFECTIVE BECAUSE OF IMPROPER MATERIAL OR WORKMANSHIP, UNDER NORMAL USE AND MAINTENANCE.

### **WHAT WILL WE DO TO CORRECT PROBLEMS?**

WE WILL REPAIR THE PRODUCT AT NO CHARGE, USING NEW OR REFURBISHED REPLACEMENT PARTS.

### **HOW LONG DOES THE COVERAGE LAST?**

THE WARRANTY PERIOD FOR PHYSICAL GOODS PURCHASED FROM WE IS 18 MONTHS FROM THE DATE OF SHIPMENT TO THE END USER.

### **WHAT DOES THIS LIMITED WARRANTY NOT COVER?**

THIS LIMITED WARRANTY DOES NOT COVER ANY PROBLEM THAT IS CAUSED BY:

- CONDITIONS, MALFUNCTIONS OR DAMAGE NOT RESULTING FROM DEFECTS IN MATERIAL OR WORKMANSHIP
- SHIPPING COST FOR REPAIR, OR DAMAGE FROM SHIPPING

### **WHAT DO YOU HAVE TO DO?**

TO OBTAIN WARRANTY SERVICE, CONTACT US TO DETERMINE THE PROBLEM AND THE MOST APPROPRIATE SOLUTION FOR YOU. IF DEFECTS ARE CONSIDERED PRODUCT MUST BE SHIPPED BY CUSTOMER TO OUTLAW INDUSTRIES, IF DEFECTS ARE COVERED UNDER WARRANTY PRODUCT WILL BE REPAIRED AND SHIPPED BACK TO CUSTOMER BY OUTLAW INDUSTRIES.

## **WARNING**

**WARNING: IMPROPER INSTALLATION, MAINTENANCE, INSPECTION OR USAGE OF THE PRODUCT OR ANY RELATED ACCESSORIES OR PARTS MAY CAUSE POSSIBLE SAFETY HAZARDS. WE WILL NOT BE LIABLE TO THE INSTALLER, PURCHASER, END USER OR ANYONE ELSE FOR DAMAGE OR INJURY TO PERSON OR PROPERTY DUE TO IMPROPER INSTALLATION, CARE, STORAGE, HANDLING, MAINTENANCE, INSPECTION, ABUSE, MISUSE OR ACT OF GOD OR NATURE INVOLVING THIS PRODUCT OR ANY RELATED ACCESSORIES OR PARTS.**